



## MULTIGRADE 20W-50



**DESCRIPTION** MULTIGRADE 20W-50 is a very high-quality mineral engine oil, which is suitable for most of 4-stroke gasoline and diesel cars and light trucks. By its selected composition, a very good resistance to oxidation and optimal detergent and dispersion properties are obtained. A strong oil film guarantees a high lubricating power.

**APPLICATIONS** This oil can be applied in modern 4-stroke gasoline (multi valves, turbo, etc.) and 4-stroke diesel engines, with or without turbo. Total engine protection: engine protection and cleanliness.

### SPECIFICATIONS

ACEA	A3/B3-10	VW	505 00/501 01
ACEA	A3/B4-08	MB	229.1
API	SL/CF		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Results
Density at 15°C	ASTM D4052	g/ml	0.890
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	155
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	18.0
Viscosity index	ASTM D2270		125
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8.3
Pour point	ASTM D6892	°C	-24
CCS viscosity at -15°C	ASTM D5293	mPa.s	8800
Sulfated Ash	ASTM D874	Mass %	1,03
Flash Point COC	ASTM D92	°C	235

**BELGO-AMERICAN OIL STORAGE N.V BELCO MOTOR OIL.**

Wijnegembaan 6, Antwerp – Belgium

E-mail: [contact@belcomotoroils.com](mailto:contact@belcomotoroils.com)

Tel: +32 3 658 45 53

[www.belcomotoroils.com](http://www.belcomotoroils.com)