



SYNTURO 0W-20 C5



DESCRIPTION SYNTURO 0W-20 is a full synthetic lubricant mandatory for the newest engines of VW/Audi. It is developed to prolong the life and maintain the efficiency of emission systems. It is also designed to provide outstanding engine cleanliness, wear protection and strong durability to keep your engine running like new. A substantial fuel saving is reached through the use of the ultra low 0W20 viscosity grade.

APPLICATIONS This product is developed for mandatory use in the newest 2.0 TFSI 140 kW and 3.0 TDI CR 160 kW engines of VW and Audi which require the VW specification 508 00 and 509 00. Total engine protection: performance in keeping the engine clean. Fuel economy: superior fuel economy and CO2 reduction. Cold start: excellent fluidity at low temperature.

SPECIFICATIONS

ACEA	C5	VW	508.00/509.00
PORSCHE	C20	VW	TL 52 577

TYPICAL CHARACTERISTICS

Test	Method	Unit	Results
Density at 15°C	ASTM D4052	g/ml	0.835
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	40.2
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.2
Viscosity index	ASTM D2270		184
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8.3
Pour point	ASTM D6892	°C	-51
Sulfated Ash	ASTM D874	Mass %	0.79
Flash Point COC	ASTM D92	°C	235
Colour	VIZUAL		GREEN
CCS viscosity at -35°C	ASTM D5293	mPa.s	3500

BELGO-AMERICAN OIL STORAGE N.V BELCO MOTOR OIL.

Wijnegembaan 6, Antwerp – Belgium

E-mail: contact@belcomotoroils.com

Tel: +32 3 658 45 53

www.belcomotoroils.com